
System	Climate® Moisture Shield Powder Coating	
Substrate	Plywood sheathing	
Use	Water resistive barrier coating on sheathing	
VOC Content	Nil	
Colour Name	Desert Sand	
Finish	Low sheen fine texture	
Test Results	Vapour resistance ASTM E96b	Pass
	Accelerated weathering (QUV 1000 hrs)	Pass
	Resistance to water penetration AS/NZS 4201.4	Pass
Outdoor Exposure Period	Suitable for up to 180 days	

Features	Permeability promotes panel drying	
	Effective water and moisture drainage	
	Board edges coated for greater moisture protection	
	VOC free, low waste powder coating technology	
	Outdoor durable resin system for exterior performance up to 180 days prior to the installation of the cladding	
Limitations	Must be covered by the cladding within 6 months of installation.	
	Do not use active organic solvents on the coating such as Thinners, MEK	
Health and Safety	Refer to Carter Holt Harvey Plywood Limited for MSDS	
	New Zealand www.chply.co.nz	
Technical Support	Climate Coating Ltd Phone +64 9 256 7879	

The information contained in this brochure must not be reproduced or published in whole or in part without prior written approval of Climate Coating Ltd.
Climate Coating Ltd reserves the right to revise without notice any information contained in this technical data sheet. Please contact Climate Customer Services Department for the latest information.
Technical information given verbally or in writing is based on knowledge and research, given in good faith and believed to be reliable, but no guarantee of accuracy is made or implied. Since methods and conditions of use are beyond our control, all products and services are sold and received subject to the condition that our liability whether express or implied for any defect in quality, or for any lack of fitness for the specified use thereof, is limited to the return of the purchase price if written claim is made within 14 days from date of delivery. It is recommended that the user makes their own tests to determine the suitability of the product for their own requirements.