



INSTALLATION TIPS FOR ECOPLY® BARRIER



EFFECTIVE ASSURANCE AGAINST BUILDING ENVELOPE LEAKS

Used in residential and commercial buildings Ecoply® Barrier rigid air barrier replaces traditional building wrap in drained cavity wall systems providing both high structural bracing and a strong protective barrier against moisture leaks into the building envelope.

Working with Ecoply Barrier is easy and when used to its full potential provides significant build advantages compared to conventional construction methods.

For more information including CAD Details & the latest Ecoply Barrier Specification Installation Manual, you can visit our website on www.chhwoodproducts.co.nz in the "Library" section.

- **Incorporate into plans early to reduce total build cost**
Use Ecoply Barrier as both a rigid air barrier and structural bracing to significantly reduce the amount of internal building bracing required

- **Build faster in any weather**
Ecoply Barrier provides early building close in allowing an early start on internal fit out work No more on site delays waiting for the cladding installation. Compared to traditional building wrap systems Ecoply Barrier can save up to 2–4 weeks in total project construction time ¹
- **Extra flexibility during construction**
Ecoply Barrier can be left exposed to the elements for up to 90 days for even greater build flexibility as well as being ideal for retrofit projects where bracing from internal linings may have been compromised
- **Fasteners**
Stainless steel fasteners are only required in sea spray zones, in all other areas (including bracing elements) use hot dipped galvanised fasteners to reduce construction costs

¹Time saving is based on the total average build time of a single level 120 m² brick and tile residential building on cavity construction with timber framing on a concrete base.



Information contained in this document is specific to the CHH Woodproducts range of plywood products and cannot be used with any other plywood products no matter how similar they may appear.

For further information contact customer services or visit www.chhwoodproducts.co.nz

0800 326 759
www.chhwoodproducts.co.nz